


P-LIGHT 27

wall and ceiling light, emergency exit light, LED, 6000K, white, L/W/H 26.5/4.5/21 cm, 3,5W

The P-LIGHT 27 emergency lighting system is suitable for use as a wall and ceiling light. The safety lights are fitted with a built-in Ni-MH battery with an automatic self-test. The detection range is 24 m. The emergency operating time of the luminaires is three hours. The luminaires can be operated permanently switched on / stand-by operation. The luminaire is connected directly to the 230V mains supply. Other variants of the P-LIGHT series are available. The luminaire is supplied with three signs with different arrow directions (right / left / down). As an option, other signs are available.



TECHNICAL DATA

Item no.:	240000
Lamps included	0
Number of different light outlets	1
Primary nominal voltage	220-240V ~50Hz mA/V
Width	26.5 cm
Height	21.0 cm
Depth	4.5 cm
Net weight	0.84 kg
Gross weight	0.99 kg
Safety class	II
Assembly	Surface
Assembly details	Ceiling, Wall
Wattage	3.5 W
Lumen	32 lm
Colour temperature	6000 Kelvin
CRI	>70
Service life	25000 h
BIG WHITE Page	740

Accessories

240007	PICTOGRAM FOILS , for P-LIGHT emergency exit light, set of 4, diagonal arrow in all directions, L/H 24/13.1 cm
240020	RECHARGEABLE BATTERY , for P-LIGHT, 3.6V, 900mA

Notes
